

## Auto-Lock Tech Specs.

| Part #     | Material | Gate Opening    | Rating      | Outside Length   | Outside Width   | Min. Breaking Strength | Weight           |
|------------|----------|-----------------|-------------|------------------|-----------------|------------------------|------------------|
| 432375     | Aluminum | .875" (22.2 mm) | CE & UIAA   | 5.25" (133 mm)   | 2.5" (63.5 mm)  | 7,418 lbf. (33 kN)     | 4.6 oz. (130 g)  |
| Biner8     | Aluminum | .787" (20 mm)   | NFPA "L"    | 4.48" (113.8 mm) | 2.78" (70.6 mm) | 6,744 lbf. (30 kN)     | 3.9 oz. (111 g)  |
| Biner8-R   | Aluminum | .787" (20 mm)   | NFPA "L"    | 4.48" (113.8 mm) | 2.78" (70.6 mm) | 6,744 lbf. (30 kN)     | 3.9 oz. (111 g)  |
| Biner8-RC  | Aluminum | .787" (20 mm)   | NFPA "L"    | 4.48" (113.8 mm) | 2.78" (70.6 mm) | 6,744 lbf. (30 kN)     | 3.9 oz. (111 g)  |
| Biner9     | Aluminum | .94" (24 mm)    | None        | 4.5" (114.3 mm)  | 3.15" (80 mm)   | 5,170 lbf. (23 kN)     | 3.7 oz. (105 g)  |
| Biner10    | Steel    | .945" (24 mm)   | None        | 4.38" (111.3 mm) | 2.77" (70.4 mm) | 11,900 lbf. (53 kN)    | 7.4 oz. (210 g)  |
| Biner10-C  | Steel    | .945" (24 mm)   | None        | 4.38" (111.3 mm) | 2.77" (70.4 mm) | 11,900 lbf. (53 kN)    | 7.7 oz. (218 g)  |
| Biner32    | Aluminum | 1.12" (28.5 mm) | UIAA        | 4.5" (114.3 mm)  | 3.15" (80 mm)   | 5,170 lbf. (23 kN)     | 3.7 oz. (105 g)  |
| NFPA102200 | Steel    | .94" (23.8 mm)  | NFPA "G"    | 4.52" (114 mm)   | 2.76" (70.2 mm) | 10,341 lbf. (46 kN)    | 6.6 oz. (187 g)  |
| M34BL      | Aluminum | .82" (21 mm)    | CE          | 4.37" (111 mm)   | 2.5" (63 mm)    | 6,294 lbf. (28 kN)     | 2.6 oz. (75 g)   |
| M36BL      | Aluminum | 1" (25 mm)      | CE          | 4.6" (117 mm)    | 3.1" (79 mm)    | 6,294 lbf. (28 kN)     | 3 oz. (85 g)     |
| M42        | Aluminum | .59" (15 mm)    | CE & UIAA   | 4.25" (108 mm)   | 3" (78 mm)      | 5,620 lbf. (25 kN)     | 2.9 oz. (85 g)   |
| M73        | Steel    | .9" (23 mm)     | CE & EN362  | 4.75" (120 mm)   | 3.12" (79 mm)   | 8,992 lbf. (40 kN)     | 10 oz. (283 g)   |
| 102100     | Steel    | 1" (25 mm)      | ANSI Z359.1 | 4.6" (116 mm)    | 2.8" (71 mm)    | 7,000 lbf (31 kN)      | 8.9 oz. (254 g)  |
| C2LPTSR    | Aluminum | 1" (25 mm)      | NFPA "L"    | 4.37" (111 mm)   | 2.5" (63.5 mm)  | 6,294 lbf. (28 kN)     | 3.2 oz. (90.7 g) |
| SM103100N  | Aluminum | 0.98" (24.9 mm) | NFPA "L"    | 4.57" (116 mm)   | 2.85" (72.3 mm) | 6,295 lbf. 28 kN)      | 3.2 oz. (90.7 g) |
| SM130107N  | Aluminum | 0.98" (24.9 mm) | NFPA "L"    | 4.57" (116 mm)   | 2.85" (72.3 mm) | 6,295 lbf. 28 kN)      | 3.2 oz. (90.7 g) |

