

Part #	Gate	NFPA Rated	Gate Opening	Outside Length	Outside Width	Min. Breaking Strength	Weight
5960	Dbl. Locking Snap		2.5" (63mm)	9.3"	4.75"	5,000 lbf. (22.2kN)	21.6 oz. (477g)
4368	Screw		2.25" (57mm)	9.5"	4.3"	5,000 lbf. (22.2kN)	8.7oz. (244g)
9660	Dbl. Locking Snap		.75" (20mm)	5.75"	2.5"	5,000 lbf. (22.2kN)	6.6 oz. (187g)
Biner 17	Screw	"G"	2.36" (60mm)	8.8" (223.3mm)	4.4" (111.8mm)	9,217 lbf. (41kN)	24.1 oz. (683g)
Biner 18	Auto Lock	"G"	2.24" (57mm)	8.8" (223.3mm)	4.4" (111.8mm)	9,217 lbf. (41kN)	23.4 oz. (663g)
Biner 21	Screw	"G"	2.05" (52mm)	8.8" (223.3mm)	4.4" (111.8mm)	9,217 lbf. (41kN)	23.2 oz. (658g)
Biner 22	Auto Lock	"G"	2.13" (54mm)	8.8" (223.3mm)	4.4" (111.8mm)	9,217 lbf. (41kN)	23.9 oz. (678g)