

Part #	Shape	Material	Diameter	Outside Length	Gate Opening	Weight	Working Load	Min. Breaking Strength
D-100-GS	Delta	Steel	10mm	3.4" (87mm)	.468" (12mm)	5.4oz. (153g)	1,985 lbs. (902kg)	9,920 lbf. (44.12kN)
D-100-ZN	Delta	Aluminum	10mm	3.4" (87mm)	.468" (12mm)	1.9 oz. (53g)	770 lbs. (350kg)	3,860 lbf. (17.16kN)
D-120-GS	Delta	Steel	12mm	4.1" (104mm)	.593" (15mm)	8 oz. (226g)	2,425 lbs. (1102kg)	12,125 lbf. (54.3kN)
D-120-SS	Delta	Stainless	12mm	4.1" (104mm)	.593" (15mm)	9 oz. (226g)	3,860 lbs. (1,754kg)	19,290 lbf. (85.8kN)
G-030-GS	Oval	Steel	3mm	1.5" (39mm)	.31" (8mm)	1 oz. (28g)	100 lbs. (45kg)	495 lbf. (2.2kN)
G-070-GS	Oval	Steel	7mm	3.13" (79mm)	.625" (16mm)	2.2 oz. (62g)	1,100 lbs. (500kg)	5,510 lbf. (24.5kN)
G-090-GS	Oval	Steel	9mm	3.75" (95mm)	.75" (19mm)	4.9 oz. (138g)	1,760 lbs. (800kg)	8,820 lbf. (39.23kN)
G-100-GS	Oval	Steel	10mm	4.2" (105mm)	.812" (21mm)	5.6 oz. (158g)	2,205 lbs. (1002kg)	11,020 lbf. (49.01kN)
G-120-GS	Oval	Steel	12mm	4.88" (124mm)	.937" (24mm)	7.8 oz. (220g)	2,755 lbs. (1,252kg)	13,780 lbf. (61.29kN)
G-140-GS	Oval	Steel	14mm	5.6" (142mm)	1.06" (27mm)	14.7 oz. (417g)	4,410 lbs. (2,000kg)	22,045 lbf. (98.06kN)
G-160-GS	Oval	Steel	16mm	6.3" (161mm)	1.13" (29mm)	22.2 oz. (629g)	5,510 lbs. (2,499kg)	29,560 lbf. (131.5kN)
N-070-GS	Oval	Steel	7mm	2.6" (67mm)	.625" (16mm)	1.8oz. (51g)	1,210 lbs (549kg)	5,510 lbf. (24.5kN)
P-100-GS	Pear	Steel	10mm	4.6" (117mm)	.81" (21mm)	6.5 oz. (184g)	1,590 lbs. (721kg)	7,935 lbf. (35.3kN)
P-160-GS	Pear	Steel	16mm	6.9" (176mm)	1.13" (29mm)	26 oz. (737g)	4,410 lbs. (2,000kg)	22,045 lbf. (98.06kN)
S-100-GS	Semi-Circle	Steel	10mm	3.5" (89mm)	.5" (12.7mm)	5.4 oz. (153g)	1,980 lbs. (900kg)	9,900 lbf. (44.03kN)
S-100-ZN	Semi-Circle	Aluminum	10mm	3.5" (89mm)	.5" (12.7mm)	1.9 oz. (53g)	770 lbs. (350kg)	3,850 lbf. (17.12kN)